



LAND CRUISER 40 SERIES

TOYOTA

ARB DELUXE BULL BARS & WINCH BARS

Year	Type	Features	Winches	Part No.
1969-85	Winch Bar	Tow Points, Hi-lift Jack Point, Black	XD9000, M8274, M8000	3420020

IPF LIGHTS & LIGHTING ACCESSORIES

Year	Type	Part No.
1997-06	7" Round H4 Headlamp Conversion Lens (H4 Bulbs, not included)	920H ¹

¹IPF M002 headlight upgrade harness recommended when installing high performance H4 bulbs

Year	Model	Recommended Lighting
1969-85	Winch Bar	800XSD, 900XS, 900HID, 930S/R, 960S/R, 868CS, 968CS, J-01

SAFARI SNORKELS

Year	Recommended Snorkel	Part No.
1980-1985	2H, 4.0L, Diesel, Left Side Mount	SS400HF

Refer to www.safari4x4.com.au for details.

OLD MAN EMU SUSPENSION PRODUCTS

40 Series SWB	Front	Gas - Stock/Light Load (0-110lbs)	Spring	1.50"	2	CS001F	
			Shock		2	N81	
		Gas - Heavy Load (110-240lbs)	Spring	1.25"	2	CS002F	
			Shock		2	N41	
	40 Series SWB	Rear	Diesel - Light Load (0-110lbs)	Spring	1.50"	2	CS001F
				Shock		2	N81
			Diesel - Heavy Load (110-240lbs)	Spring	1.25"	2	CS002F
				Shock		2	N41
Installation		Medium Load (0lbs to GVW)	Spring	2.25"	2	CS001R	
			Shock		2	*N89/N95	
		Heavy Constant (330lbs to GVW)	Spring	2.50"	2	CS002R	
			Shock		2	N89	
	Optional	Spring Bushing Kit - 1968-80			4	OMESB30 ¹	
		Spring Bushing Kit - Post 1980			4	OMESB1 ¹	
		U Bolts			7	OMEU59A	
		U Bolt (Early Pre 1980, 25mm spring eye)			1	OMEU59B	
		U Bolt (Late Post 1980, 35mm spring eye)			1	OMEU55	
		Rear Anti Inversion Kit			1	FK08 ²	
		Steering Damper			1	OMESD23	
		Front Greasable Shackle Kit (Pre '80) 15mm pin			1	OMEGS8	
	Front Greasable Shackle Kit (Post '80) 18mm pin			1	OMEGS2		
	Rear Greasable Shackle Kit (Pre '80) 15mm pin			1	OMEGS9		
Rear Greasable Shackle Kit (Post '80) 18mm pin			1	OMEGS17			
Greasable Pin Kit (1968-80) 15mm pin			2	OMEGP8			
Greasable Pin Kit (Post '80) 18mm pin			2	OMEGP1			
Front Extra Leaf				D3XL ³			
Rear Extra Leaf				D4XL ³			
Rear Trim Spacer				TP02			

¹ OMESB30 suits 35mm spring eye and hanger bracket with 15mm shackle pin hole. OMESB1 suits 35mm spring eye and hanger bracket with 18mm shackle pin hole.

² **FK08 Anti Inversion Kit is mandatory fitment front and rear if greasable shackles are not fitted.**

³ Extra Leaf can be fitted for heavier constant load accessories

*Firmer shock

OLD MAN EMU SUSPENSION PRODUCTS

Model	Location	Description	Type	Lift	Quantity	Part No.	
45 Series	Front	Gas - Stock/Light Load (0-110lbs)	Spring	1.50"	2	CS001F	
			Shock		2	N81	
		Gas - Heavy Load (110-240lbs)	Spring	1.25"	2	CS002F	
			Shock		2	*N41/N81	
		Diesel - Heavy Load (110-240lbs)	Spring	1.25"	2	CS002F	
			Shock		2	N41	
45 Series	Rear	Medium Load (0lbs to GVW)	Spring	2.0"	2	CS003R ¹	
			Shock	2.0"	2	N42	
		Heavy Constant (880lbs to GVW)	Spring	2.0"	2	CS003R ¹	
			Shock	2.0"	2	N42	
	Installation	Spring bushing Kit (1968-80)				4	OMESB30 ²
		Spring Bushing Kit (Post '80)				2	OMESB1 ²
		Spring Bushing Kit (Post '80)				2	OMESB79 ²
		U Bolts				3	OMEU59A
		U Bolts (Early)				5	OMEU59B
		U Bolt (Late)				4	OMEU59B
		U Bolt (Late)				1	OMEU55
		Anti Inversion Kit				1	FK08 ³
		Steering Damper				1	OMESD23
	Optional	Front Greasable Shackle Kit (Pre '80)				1	OMEGS8
		Front Greasable Shackle Kit (Post '80)				1	OMEGS2
		Rear Greasable Shackle Kit (Pre '80)				1	OMEGS9
		Rear Greasable Shackle Kit (Post '80)				1	OMEGS1
		Greasable Pin Kit (1968-80)				2	OMEGP8
		Greasable Pin Kit (Post '80)				2	OMEGP1
		Front Extra Leaf					D3XL ⁴
		Rear Extra Leaf					201XL ⁴
		Rear Trim Spacer					TP02

¹ Remove 3rd leaf from CS003R spring stack to reduce spring rate for medium duty application.

² OMESB30 suits 35mm spring eye and hanger bracket with 15mm shackle pin hole. OMESB1 suits 35mm spring eye and hanger bracket with 18mm shackle pin hole. OMESB79 suits 35mm spring eye with 30mm hanger bracket with 18mm shackle pin hole.

³ FK08 Anti Inversion Kit is mandatory fitment front and rear if greasable shackles are not fitted.

⁴ Extra Leaf can be fitted for heavier constant load carrying ability. Important: Install leaf springs with military wrap at the fixed end.

ARB AIR LOCKER LOCKING DIFFERENTIALS & ACCESSORIES

<u>Year</u>	<u>Axle</u>	<u>Description</u>	<u>Shaft</u>	<u>Spline</u>	<u>Ratio</u>	<u>Part No.</u>
To 1989	Front	12 bolt, full floating	33 (1.31")	30	ALL	RD142 ²
1990-97		10 bolt, full floating	33 (1.31")	30	ALL	RD132 ⁴
1969-76 ¹	Rear	12 bolt, semi floating	33 (1.31")	30	ALL	RD124
1977-89		12 bolt, full floating 45mm bearing ID	33 (1.31")	30	ALL	RD142 ²
1990-97		12 bolt, full floating 50mm bearing ID	33 (1.31")	30	ALL	RD142
1977-92		12 bolt, semi floating	33 (1.31")	30	ALL	RD124
FJ40s ³		Dana 60	30 (1.31")	30	4.56 & UP	RD21
			30 (1.31")	30	4.10 & DN	RD22

¹ Only vehicles made in North America.

² Must use late model 50.00mm (1.969") ID bearings with this application. (ARB Part No. 160116)

³ Only FJ40s made in South America.

⁴ RD132 supercedes RD23 March 2007